



INFUSED WITH
INTERSEPT®
ANTIMICROBIAL

XL RUBBER FLOOR FINISH

Tech Data Sheet



Designed specifically for rubber flooring, **XL Rubber Floor Finish** is a flexible protective coating that is easily maintainable. SBR or recycled chip, **XL Rubber floor finish** provides a slight shine while protecting your investment. State of the art polymers along with being infused with **Intersept®** makes this product a one of a kind in the industry.

WHERE TO USE

XL Rubber Floor Finish is specially formulated for Rubber Floors but may be used on Most Resilient Floors.

DIRECTIONS

Sweep the floor first using a dust mop or hard surface vacuum. Prior to application, floor should be completely stripped of old finish and thoroughly rinsed or cleaned to an acceptable appearance. The floor should be completely dry before applying the first coat and all subsequent coats. Do not use an air mover or fan to dry finish. Using a microfiber pad or clean mop, apply 2 – 4 thin, even coats on unsealed floors. On cleaned or scrubbed floors, apply as needed. **XL Rubber Floor Finish** is a buffable product, however follow flooring manufactures recommendations regarding use of mechanical equipment on surfaces. Allow 24 hours for curing before any heavy furniture is put on the floor. Do not slide furniture on finished floor.

INTERSEPT® ANTIMICROBIAL

Intersept® is an antimicrobial preservative that protects the cured floor finish against a broad spectrum of bacteria and fungi, including odor - and stain-causing microorganisms.


Intersept® is registered with the EPA and meets stringent certification standards set by the three most recognized testing protocols related to indoor environmental quality – the State of Washington Protocol, CRI Green Label and GSA Antimicrobial Certification. Yet, despite its proven ability as a microbial inhibiting preservative, **Intersept®** is low in toxicity and contains no arsenic, heavy metals, phenols or formaldehyde.

TECHNICAL SPECIFICATIONS

COLOR:	Milk-White	PACKAGING:	4x1 Gal. Case, 5 Gal. Pail
FORM:	Liquid	TYPE:	Acrylic Polymer
SCENT:	Mild Solvent/Polymer	INITIAL GLOSS:	High
pH:	8.0	RECOAT DRYING TIME:	Minimum 30 Minutes
FLASH POINT:	None	COVERAGE:	760 - 900 sq. mts.
FOAM:	None	LEVELING:	Excellent
VISCOSITY:	Water Thin	SLIP COEFFICIENT:	0.57
STORAGE (Unopened):	1 Year @ R.T.	REMOVABILITY:	Excellent
BIODEGRADABLE:	Yes	SCUFF RESISTANCE:	Very Good
WEIGHT/GAL:	8	DETERGENT RESISTANT:	Very Good
SHIPPING CLASS:	None	DILUTION:	Use As Is

XL Rubber Floor Finish

WITHOUT Intersept®
Antimicrobial Protection



Aspergillus Mold

WITH Intersept®
Antimicrobial Protection

FOR COMMERCIAL AND INDUSTRIAL USE ONLY

©2014, Cleaner Floors, Belmont, WA, 6104, AUS

Questions or Comments:
(08) 9277 7177

www.cleanerfloors.com.au



Rev. 082012a