



Product Data Sheet

1285 - MS One-Part Vinyl Adhesive

DESCRIPTION

Spartan 1285 is a 1-part MS (Modified Silane) adhesive designed for the installation of PVC commercial and domestic sheet vinyl, LVT & LVP. It is also suitable for the installation of sanded back rubber flooring, Linoleum and Artificial Grass. It has good plasticiser resistance and protection from biodegradation, making it suitable for indoor and outdoor use in wet and dry areas.

SURFACE PREPARATION

All surfaces to be bonded should be dry, smooth, and free of any contaminants that may affect final bond including dust, paints, adhesives, and old floorcoverings. All surfaces must be prepared in accordance with current Australian Standards 1884 Floor Coverings Resilient Sheet including moisture testing. **IMPORTANT:** The minimum sub floor temperature prior to commencing preparation and adhesive application is 15°C, in cold weather, the adhesive should be slightly heated in a heated environment before use. The maximum room humidity prior to commencing adhesive application is 75%, **DO NOT** apply adhesive on subfloors with rising damp.

DIRECTIONS FOR USE

Apply adhesive using a suitable trowel as listed below for your application spread evenly to prepared substrate held at approximately 60-degree angle. Best results are when the adhesive is allowed to have between 5 – 20 minutes open time prior to installing floorcovering into a wet film of adhesive. This timespan will depend on atmospheric conditions. Always ensure complete transfer of adhesive to the floorcovering has occurred. Complete installation according to manufacturer's instructions and current AS1884 standards.

Roll installation prior to adhesive setting with the recommended weight roller.

Do not allow traffic or water for 24 hours after installation.

CLEAN UP

Clean tools immediately after use with Adhesive Remover. Dried adhesive may be softened using a suitable solvent.



Note: Do not use solvent cleaners on floorcoverings.

SHELF LIFE

Up to 12 months in sealed container and stored at 20°C.

Air time: 5 – 20 minutes.

Working Time: Up to 35 minutes depending on site conditions.

Curing Time: 24 – 48 hours.

COVERAGE of 7.5kg pail LVT vinyl and PVC with smooth back surface using a V1 notched trowel - Up to 27 m² per pail Linoleum, rubber and PVC flooring with textured back surface using a V2 notched trowel - Up to 16 m² per pail Synthetic grass, needle fleece flooring using a V3, or larger notch required on very textured products - Up to 10 m² per pail

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling, and transport is available in the Safety Data Sheet (SDS), available on request.

KEVMOR
TRADE SUPPLIES
www.kevmor.com.au

Kevmor Trade Supplies

11 Belmont Avenue, Belmont WA 6104

P: 08 9277 7177

E: sales@kevmor.com.au