



Product Data Sheet

1410 - Premium Vinyl Adhesive

DESCRIPTION

Spartan 1410 is a premium, high performance low VOC acrylic based adhesive designed for the installation of commercial and domestic sheet vinyl. It has excellent plasticiser resistance and is formulated to provide quick initial grab and exhibit excellent 're-bond' characteristics. Internal use only.

SURFACE PREPARATION

All surfaces to be bonded should be dry, smooth, and free of any contaminants that may affect final bond. This includes dust, old adhesives, and old floorcoverings.

All surfaces must be prepared and installed in accordance with Australian Standards AS 1884:2021 Floor Coverings Resilient Sheet including moisture and pH testing.

It is recommended that all highly absorbent sub floors be primed with a suitable acrylic floor primer prior to the application of adhesive.

The minimum sub floor temperature prior commencing preparation or adhesive application is 10°C.

The subfloor must be absorbent to allow adhesive to dry and cure adequately.

DIRECTIONS FOR USE

Apply adhesive using a 1.6mm x 1.6mm x 1.6mm "V" notched spreader. Coverage should be in the vicinity of 5m² per litre.

Some domestic sheet vinyls may require a fine 1.6mm x 0.8mm x 0.8mm "U" notched trowel to prevent adhesive 'show through'.

Adhesive can be allowed to tack-up prior to placing the floor covering into wet film of adhesive. Tack-up time will depend on atmospheric conditions.

Complete installation according to manufacturer's instructions Roll installation with the recommended weight roller prior to the adhesive setting.



Do not allow heavy traffic for 24 hours.

Seams of domestic vinyl should be sealed using Spartan 1230 Vinyl Seam-Sealer.

CLEAN UP

Clean tools immediately after use with warm soapy water.
Dried adhesive may be softened using a suitable solvent.

SHELF LIFE

Up to 12 months in sealed container and stored at 20°C.

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling, and transport is available in the Safety Data Sheet (SDS), available on request.

KEVMOR
TRADE SUPPLIES
www.kevmor.com.au

Kevmor Trade Supplies

11 Belmont Avenue, Belmont WA 6104

P: 08 9277 7177

E: sales@kevmor.com.au