



Product Data Sheet

1435 - Vinyl Plank Adhesive

DESCRIPTION

Spartan 1435 is low VOC adhesive that exhibits a strong affinity with PVC. It cures to form a hard film as defined by the Australian Standards AS 1884:2021 Floor Coverings Resilient Sheet. It is a high performance polymer blend adhesive designed for the installation of commercial and domestic PVC planks and tiles. It is also suitable for use on sheet vinyl floorcoverings. Subfloors must be absorbent. It has an excellent plasticizer resistance and is formulated to provide quick initial grab. Internal use only.

SURFACE PREPARATION

All surfaces to be bonded should be dry, smooth, and free of any contaminants that may affect final bond. This includes dust, old adhesives, and old floorcoverings.

All surfaces must be prepared and installed in accordance with current Australian Standards AS 1884:2021 Floor Coverings Resilient Sheet including moisture and pH testing.

It is recommended that all highly absorbent sub floors be primed with suitable Acrylic Floor & Wall Primer prior to the application of adhesive.

The minimum sub floor temperature prior to commencing preparation or adhesive application is 10°C.

DIRECTIONS FOR USE

The installation area, floorcovering and substrate should be kept at the appropriate temperature as required by the floorcovering manufacturer and section 4 of the current Australian/NZ Standard 1884. The key to a successful installation is consistent temperatures being maintained 48 hours prior to installation, during and 48 hours after installation.

Spread adhesive with a 1.6mm x 1.6mm x 1.6mm 'V' Notched trowel. When installing PVC planks and Tiles lay floorcovering into adhesive without allowing any tack-up time. When installing vinyl sheet products adhesive can be allowed to have a very short tack-up time before floorcoverings is lowered. Always



check to ensure that complete transfer of adhesive to the floorcovering has occurred.

Complete installation according to vinyl manufacturer's instructions, ensuring the installation is rolled in both directions with the recommended roll weight, prior to the adhesive setting.

Do not allow heavy traffic for 24 hours.

CLEAN UP

Clean tools immediately after use with warm soapy water.
Dried adhesive may be softened from tools using a suitable solvent.

SHELF LIFE

Up to 12 months in sealed container and stored at 20°C

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling, and transport is available in the Safety Data Sheet (SDS), available on request.

KEVMOR
TRADE SUPPLIES
www.kevmor.com.au

Kevmor Trade Supplies

11 Belmont Avenue, Belmont WA 6104

P: 08 9277 7177

E: sales@kevmor.com.au