

AW 901

CLEANER/THINNER

8 December 2017

DESCRIPTION

AW 901 Cleaner/Thinner is a specifically formulated solvent blend that is ideally suited for cleaning off dried water based and solvent based adhesives, such as spillage and adhesive overspray's.

AW 901 Cleaner/Thinner is especially suitable for use with solvent based contact adhesives adhesives.

USES

As a thinner for AW brush, roller, and scraper grade contact adhesives.

For thinning spray contacts it is generally not required. For cleaning metal tools.

Cleaning/Soaking metal spray gun parts and scrapers.

APPLICATION INTRUCTIONS

AW 901 should be applied directly to dried adhesive to soften the film, followed by removal by gradually scraping or wiping the adhesive away.

Spills and overspray can be removed by wiping with a rag soaked in AW 901.

As a thinner, AW 901 is formulated to thin AW solvent based contact adhesives 101R, 2700/2701.

LIMITATIONS

- Do not use on expanded polystyrene foam.
- Do not use on PVC, ABS, Styrene or similar plastic surfaces.
- Do not use to thin adhesives used for polystyrene foam, AW 1830/1831.

STORAGE & SHELF LIFE

Store in a cool, dry place, out of direct sunlight and away from all sources of ignition. Storage areas must be well ventilated and comply with Local, State and Federal regulations. For maximum shelf life, store between 5°C and 20°C.

HEALTH & SAFETY

Please refer to the SDS which is available online. The solvents contained within this product are Highly Flammable

PRODUCT CHARACTERISTICS	
Appearance	Water Clear
Base	Blend of hydrocarbon and Ketone solvents
Shelf Life	Approximately 1 year in original sealed container at 20°C
Flash Point	Less than 0°C
Product code 20 Litre	30840552

Version 5 Page **1** of **2**

AW 901 CLEANER/THINNER

For emergency information contact the Poisons Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.





Kevmor Trade Supplies
11 Belmont Avenue, Belmont WA 6104
P: 08 9277 7177 E: sales@kevmor.com.au

This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.com/au

Bostik Australia Pty Ltd, Level 1, 6 English St, Essendon Fields, Vic, 3041, Australia. Tel: +613 9279 9333 www.bostik.com.au