



ARDEX MULTIPRIME

Water-Based Primer

Improves adhesion to various substrates

For internal and external, walls and floors

Water-based - no solvent hazard

Quick drying - apply subsequent products sooner

Low VOC content - meets Green Building Council of Australia Green Star IEQ-13 requirements

ARDEX Australia Pty Ltd
20 Powers Road
Seven Hills NSW 2147
Tel: (02) 9851 9199
Fax: (02) 9674 5621
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX New Zealand Ltd
32 Lane St, Woolston
Christchurch, New Zealand
Tel: (03) 384 3029
Fax: (03) 384 9779
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX MULTIPRIME

Water-Based Primer

DESCRIPTION

ARDEX Multiprime is a water-based primer used for improving the adhesion of ARDEX products to various porous substrates. It is easy to apply with a sponge, brush or roller with applications of subsequent products able to take place with minimal downtime.

ARDEX Multiprime is suitable for both internal and external, wall or floor applications.

FOR USE WITH

ARDEX Multiprime is compatible with subsequent applications of ARDEX tile adhesives, floor levelling compounds and undertile waterproofing membranes.

TO (SUBSTRATES)

Medium density fibre-cement sheet, compressed fibre-cement sheet
Jointing compound over plasterboard
Concrete, renders, screeds
Masonry and lightweight concrete blocks
Autoclaved aerated concrete (AAC)

Contact ARDEX if other substrates are encountered.

SUBSTRATE PREPARATION

The surface to be primed must be clean, firm and free of dust, dirt, oil, grease, curing compounds, release agents and other barrier materials.

Ensure surfaces are dry prior to application, with no residue or permanent damp.

Surfaces must be suitable for the application of the subsequent product being used.

APPLICATION

Shake contents and ARDEX Multiprime is ready for use. Sponge, brush or roll ARDEX Multiprime liberally over the entire surface to be sealed.

For very porous surfaces a second coat of ARDEX Multiprime is required, such as autoclaved aerated concrete.

All tools should be cleaned with water immediately after use.

DRYING TIME

Ensure the ARDEX Multiprime is fully dry prior to the application of subsequent products, allow approximately 15-30 minutes at 23°C and 50% relative humidity.

Type of substrate being primed, porosity and climatic conditions will affect drying times, allow longer for lower temperatures or high relative humidity.

COVERAGE

One litre of ARDEX Multiprime is sufficient for approximately 6m², therefore the approximate coverage on each of the following units is:

20L - 120m²
4L - 24m²
1L - 6m²

Coverage will vary depending on the porosity of the surface and method of application.

PACKAGING

ARDEX Multiprime is packed in plastic pails - net volume 1L, 4L and 20L.

SHELF LIFE

ARDEX Multiprime has a shelf life of not less than 12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity.

Store away from direct sunlight. Replace lid tightly after use.

Pay attention to the following:

ARDEX Multiprime is not suitable for use on glazed, impervious or silicone treated surfaces.

Metal surfaces must be primed with an appropriate metal primer.

Do not empty excess primer back into the original packaging as this may cause contamination of the contents.

SAFETY PRECAUTIONS

This product is considered non hazardous and non toxic in normal usage.

Avoid contact with skin and eyes; in case of contact with the eyes, rinse immediately with plenty of water and seek medical advice; wear suitable gloves and eye protection and keep the product out of the reach of children. If swallowed do not induce vomiting, give a glass of water and contact a doctor.

For further material safety data, consult the latest Material Safety Data Sheet.

TECHNICAL DATA

| | |
|--|-------------------------------|
| Colour: | White |
| Mixing Ratio: | No mixing |
| Coverage: | Approx 6m ² /litre |
| Drying Time: (at 23°C and 50% relative humidity) | Approx 15-30 minutes |
| pH: | 8-9 |

KEVMOR

TRADE SUPPLIES

Kevmor Trade Supplies

11 Belmont Avenue, Belmont WA 6104
P: 08 9277 7177
E: sales@kevmor.com.au
W: kevmor.com.au

ARDEX Australia Pty Ltd

| | | |
|---------|-------------------|--------------------|
| NSW | Ph (02) 9851 9100 | Fax (02) 9838 7970 |
| QLD | Ph (07) 3817 6000 | Fax (07) 3881 3188 |
| VIC/TAS | Ph (03) 9308 9255 | Fax (03) 9308 9332 |
| SA | Ph (08) 8268 2511 | Fax (08) 8345 3207 |
| WA | Ph (08) 9256 8600 | Fax (08) 9455 1227 |

ARDEX New Zealand Ltd

| | | |
|--------------|------------------|-------------------|
| Auckland | Ph (09) 2967 690 | Fax (09) 2967 689 |
| Wellington | Ph (04) 5685 949 | Fax (04) 5686 376 |
| Christchurch | Ph (03) 3843 029 | Fax (03) 3849 779 |

Technical Services Toll Free: 1800 224 070

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.
© ARDEX Australia Pty Ltd 2009.
All aforementioned products are the trade marks of ARDEX Australia Pty Ltd, its licensors and affiliates.