

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT Revision Number 3.01

Revision date 23-May-2022 Supersedes Date: 01-Sep-2021

Section 1: Identification: Product	identifier and chemical identity	
Product identifier		
Product Name	ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT	
Product Code(s) 30800828 30800828		
Other means of identification		
Pure substance/mixture	Mixture	
Recommended use of the chemica	al and restrictions on use	
Recommended use	Sealant	
Uses advised against	No information available	
Details of manufacturer or importe	<u>er</u>	
Supplier Bostik Australia Pty Ltd 51-71 High Street, Thomastown Victoria Australia Tel: 613 9279-9333 Fax: 613 9279-9342		
ABN: 79 003 893 838		
E-mail address	au-bostik-sds@bostik.com	
Emergency telephone number		
Emergency telephone number	24-hr Emergency: 1800 033 111	
Section 2: Hazard(s) identification		
GHS Classification		
Carcinogenicity	Category 2 - (H351)	
Specific target organ toxicity (sing	gle exposure) Category 2	
Label elements_		

Health hazard



ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT

Revision Number 3.01

Revision date 23-May-2022 Supersedes Date: 01-Sep-2021

Signal word WARNING

Hazard statements

H351 - Suspected of causing cancer H371 - May cause damage to organs

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/clothing and eye/face protection Do not breathe dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product **Precautionary Statements - Response** IF exposed or concerned: Get medical advice/attention IF exposed or concerned: Call a POISON CENTER or doctor **Precautionary Statements - Storage** Store locked up **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing. Causes mild skin irritation.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No	Weight-%
2-Butanone, O,O',O"-(methylsilylidyne)trioxime	22984-54-9	< 5%
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	< 2 %
2-Butanone, oxime	96-29-7	< 2%
Toluene	108-88-3	< 0.5%
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures	
Emergency telephone number	Poisons Information Center, Australia: 13 11 26 Poisons Information Center, New Zealand: 0800 764 766
Description of first aid measures	
General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a physician.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT Revision Number 3.01

Skin contact	Wash off immediately with plenty of water for at least 15 minutes. If symptoms persist, call a physician.	
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.	
Most important symptoms and effects, both acute and delayed		
Symptoms	None known.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.	

Section 5: Firefighting measures	
Suitable Extinguishing Media	
Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet.
Specific hazards arising from the chemical	
Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapors.
Hazardous combustion products	Carbon dioxide (CO2). Nitrogen oxides (NOx). Silicon oxides.
Special protective actions for fire-	fighters
Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.
Section 6: Accidental release mea	sures
Personal precautions, protective e	equipment and emergency procedures
Personal precautions	Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.
Other information	Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.
Environmental precautions	
Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.
Methods and material for containment and cleaning up	
Methods for containment	Do not scatter spilled material with high pressure water streams.
Methods for cleaning up	Pick up and transfer to properly labeled containers.
Precautions to prevent secondary hazards	

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT Revision Number 3.01

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.	
General hygiene considerations	Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off contaminated clothing and wash it before reuse.	
Conditions for safe storage, including any incompatibilities		
Storage Conditions	Protect from moisture. Keep away from food, drink and animal feeding stuffs.	
Recommended storage temperature	Keep at temperatures between 50 and 95 $^{\circ}\text{F}$ / 10 and 35 $^{\circ}\text{C}.$	
Incompatible materials	Strong oxidizing agents.	
Section 8: Exposure controls and personal protection		

Control parameters

Exposure Limits

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Chemical name	Australia
Toluene	TWA: 50 ppm
108-88-3	TWA: 191 mg/m ³
	STEL: 150 ppm
	STEL: 574 mg/m ³

OEL as published by Safe Work Australia

Biological occupational exposure limits

Appropriate engineering controls

Engineering controls	Showers, eyewash stations, and ventilation systems.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear suitable protective clothing.
Hand protection	Wear suitable gloves.
Respiratory protection	Organic gases and vapors filter conforming to EN 14387. White. Brown.
Environmental exposure controls	No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Paste / Gel Liquid
Appearance	Viscous
Color	Clear
Odor	Organic
Odor threshold	No information available

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT Revision Number 3.01

Revision date 23-May-2022 Supersedes Date: 01-Sep-2021

Property	Values	Remarks • Method
рН	No data available	Not applicable Insoluble in water
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	
Initial boiling point and boiling	No data available	
range		
Flash point	No data available	
Evaporation rate	No data available	
Flammability	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive	No data available	
limits		
Lower flammability or explosive	No data avallable	
limits Vapor pressure	No data available	
Relative vapor density	No data available	
Relative density	1.01	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	150000 250000 mPa s	
Explosive properties	No information available	
Oxidizing properties	No information available	
Other information		
Solid content (%)	No information available	
Density	No information available	nation available
VOC Content (%)		Tation available
Section 10: Stability and reactivity	1	
	1	
Section 10: Stability and reactivity Reactivity	1	
Reactivity		
	Product cures with moisture.	
Reactivity		
<u>Reactivity</u> Reactivity	Product cures with moisture.	
<u>Reactivity</u> Reactivity		
Reactivity Reactivity <u>Chemical stability</u> Stability	Product cures with moisture.	
Reactivity Reactivity <u>Chemical stability</u> Stability Explosion data	Product cures with moisture. Stable under normal conditions.	
Reactivity Reactivity <u>Chemical stability</u> Stability Explosion data Sensitivity to mechanical	Product cures with moisture.	
Reactivity Reactivity <u>Chemical stability</u> Stability Explosion data Sensitivity to mechanical impact	Product cures with moisture. Stable under normal conditions. None.	
Reactivity Reactivity <u>Chemical stability</u> Stability Explosion data Sensitivity to mechanical	Product cures with moisture. Stable under normal conditions.	
Reactivity Reactivity <u>Chemical stability</u> Stability Explosion data Sensitivity to mechanical impact	Product cures with moisture. Stable under normal conditions. None. None.	
Reactivity Reactivity <u>Chemical stability</u> Stability Explosion data Sensitivity to mechanical impact Sensitivity to static discharge Possibility of hazardous reactions	Product cures with moisture. Stable under normal conditions. None. None.	
Reactivity Reactivity <u>Chemical stability</u> Stability Explosion data Sensitivity to mechanical impact Sensitivity to static discharge	Product cures with moisture. Stable under normal conditions. None. None.	
Reactivity Reactivity <u>Chemical stability</u> Stability Explosion data Sensitivity to mechanical impact Sensitivity to static discharge Possibility of hazardous reactions	Product cures with moisture. Stable under normal conditions. None. None.	
Reactivity Reactivity Chemical stability Stability Stability Explosion data Sensitivity to mechanical impact Sensitivity to static discharge Possibility of hazardous reactions Possibility of hazardous reactions Conditions to avoid	Product cures with moisture. Stable under normal conditions. None. None.	n air or moisture over prolonged periods. Do not freeze
Reactivity Reactivity Chemical stability Stability Stability Explosion data Sensitivity to mechanical impact Sensitivity to static discharge Possibility of hazardous reactions Possibility of hazardous reactions	Product cures with moisture. Stable under normal conditions. None. None. None under normal processing.	b air or moisture over prolonged periods. Do not freeze.
Reactivity Reactivity Chemical stability Stability Stability Explosion data Sensitivity to mechanical impact Sensitivity to static discharge Possibility of hazardous reactions Possibility of hazardous reactions Conditions to avoid	Product cures with moisture. Stable under normal conditions. None. None.	
Reactivity Reactivity Chemical stability Stability Stability Explosion data Sensitivity to mechanical impact Sensitivity to static discharge Possibility of hazardous reactions Possibility of hazardous reactions Conditions to avoid	Product cures with moisture. Stable under normal conditions. None. None. None under normal processing.	
Reactivity Reactivity Chemical stability Stability Stability Explosion data Sensitivity to mechanical impact Sensitivity to static discharge Possibility of hazardous reactions Possibility of hazardous reactions Conditions to avoid Conditions to avoid Incompatible materials	Product cures with moisture. Stable under normal conditions. None. None. None under normal processing. Protect from moisture. Exposure to Keep away from open flames, hot	
Reactivity Reactivity Chemical stability Stability Stability Explosion data Sensitivity to mechanical impact Sensitivity to static discharge Possibility of hazardous reactions Possibility of hazardous reactions Conditions to avoid Conditions to avoid	Product cures with moisture. Stable under normal conditions. None. None. None under normal processing.	
Reactivity Reactivity Chemical stability Stability Stability Explosion data Sensitivity to mechanical impact Sensitivity to static discharge Possibility of hazardous reactions Possibility of hazardous reactions Conditions to avoid Conditions to avoid Incompatible materials Incompatible materials	Product cures with moisture. Stable under normal conditions. None. None. None under normal processing. Protect from moisture. Exposure to Keep away from open flames, hot Strong oxidizing agents.	
Reactivity Reactivity Chemical stability Stability Stability Explosion data Sensitivity to mechanical impact Sensitivity to static discharge Possibility of hazardous reactions Possibility of hazardous reactions Conditions to avoid Conditions to avoid Incompatible materials	Product cures with moisture. Stable under normal conditions. None. None. None under normal processing. Protect from moisture. Exposure to Keep away from open flames, hot Strong oxidizing agents.	

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT

Revision Number 3.01

Hazardous decomposition products	Carbon oxides. 2-Butanone, oxime. Methyl alcohol. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.
-------------------------------------	--

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Specific test data for the substance or mixture is not available. Causes mild skin irritation.
Ingestion	Based on available data, the classification criteria are not met.
Symptoms	Prolonged contact may cause redness and irritation.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butanone,	LD50 = 2463 mg/Kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	-
O,O',O''-(methylsilylidyne)trioxi	(OECD 401)	(OECD 402)	
me			
N-(3-(trimethoxysilyl)propyl)eth	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44
ylenediamine			mg/L air
2-Butanone, oxime	=100 mg/kg (ATE)	1000 - 1800 mg/kg	>4.83 mg/L (Rattus) 4 h
		(Oryctolagus cuniculus)	
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus	>20 mg/L (Rattus) 4 h
		cuniculus)	

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met. Classification based on data available for ingredients. Causes mild skin irritation.

Component Information					
Toluene (108-88-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No.	Rabbit	Dermal			Irritant
440/2008, Annex, B.4					

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Component Information			
Toluene (108-88-3)			
Method	Species	Exposure route	Results
Regulation (EC) No. 440/2008,	Guinea pig		No sensitization responses

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT

Revision Number 3.01

Revision date 23-May-2022 Supersedes Date: 01-Sep-2021

Germ cell mutagenicity

No information available.

Component Information			
Toluene (108-88-3)	Toluene (108-88-3)		
Method	Species	Results	
Regulation (EC) No. 440/2008, Annex, B.13/14	Salmonella typhimurium	Not mutagenic	
(Ames test)			
OECD Test No. 476: In vitro Mammalian Cell	Mouse	Not mutagenic	
Gene Mutation Test		-	

Carcinogenicity

Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia	European Union	IARC
2-Butanone, oxime 96-29-7	Carc. 2	Carc. 1B	
Toluene 108-88-3			Group 3

Legend

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Component Information			
2-Butanone, oxime (96-29-7)			
Method	Species	Results	
OECD Test No. 453: Combined Chronic	Rat	Carcinogenic	
Toxicity/Carcinogenicity Studies		-	

Reproductive toxicity

No information available.

Component Information		
Toluene (108-88-3)		
Method	Species	Results
OECD 407	in vivo	Reproductive toxicant

STOT - single exposure

Based on the classification criteria of the Globally Harmonized System as adopted in the country or region with which this safety data sheet complies, this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). May cause damage to organs.

STOT - repeated exposure

No information available.

Component Information					
Toluene (108-88-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No.	Rat, male, female	Oral		91 days	NOAEL: 625 mg/kg
440/2008, Annex, B.26					
OECD Test No. 453:	Rat, male, female	Inhalation, vapor			NOAEL: 1.131 mg/l
Combined Chronic					
Toxicity/Carcinogenicity					

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT

Revision Number 3.01

Studies			

Aspiration hazard

Based on available data, the classification criteria are not met.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
2-Butanone, O,O',O''-(methylsilylidyn e)trioxime 22984-54-9 N-(3-(trimethoxysilyl)pro pyl)ethylenediamine	subcapitata) OECD 201	EC50 (96h) >120 mg/L (Oncorhynchus mykiss)Freshwater static (OECD guideline 203) LC50 (96H) =597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) > 120 mg/L (Daphnia magna) OECD 202 EC50 (48h) =81mg/L Daphnia magna Static
1760-24-3 2-Butanone, oxime 96-29-7	EC50: =83mg/L (72h, Desmodesmus subspicatus)	LC50: =760mg/L (96h, Poecilia reticulata) LC50: 777 - 914mg/L (96h, Pimephales promelas) LC50: 320 - 1000mg/L (96h, Leuciscus idus)	EC50 = 281 mg/L 17 h EC50 = 950 mg/L 5 min	EC50: =750mg/L (48h, Daphnia magna)
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)

Persistence and degradability

Persistence and degradability

Not readily biodegradable. Product cures with moisture.

Bioaccumulative potential

Bioaccumulation

There is no data for this product.

Component Information

Chemical name	Partition coefficient
2-Butanone, O,O',O"-(methylsilylidyne)trioxime 22984-54-9	1.69
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-0.3
2-Butanone, oxime 96-29-7	0.65
Toluene 108-88-3	3.93

Mobility

Mobility in soil

No information available.

Mobility

No information available.

Other adverse effects

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT

Revision Number 3.01

Other adverse effects	No information available.			
Section 13: Disposal considerations				
Disposal methods				
Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.			
Contaminated packaging	Handle contaminated packages in the same way as the product itself.			
Section 14: Transport information				
ADG	Not regulated			
IATA	Not regulated			
IMDG_	Not regulated			

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

Saction	15. Pogulator	y information
Section	15. Regulator	y mormation

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

<u>Australia</u>

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP) No poisons schedule number allocated

Poison Schedule Number Not applicable

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Toluene	10 tonne/yr Threshold category 1
108-88-3	20 MW Threshold category 2b total
	60000 MWH Threshold category 2b total
	1 tonne/h Threshold category 2a total
	25 tonne/yr Threshold category 1a total
	400 tonne/yr Threshold category 2a total
	2000 tonne/yr Threshold category 2b total

International Inventories

AIIC	Listed
NZIOC	Listed
ENCS	Not Listed
IECSC	Not Listed
KECL	Listed
PICCS	Listed

Legend:

AIIC - Australian Inventory of Industrial Chemicals **NZIOC** - New Zealand Inventory of Chemicals

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT

Revision Number 3.01

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information		
Prepared By	Product Safety & Regulatory Affairs	
Revision date	23-May-2022	
Revision Note ***Indicates updated data since	e last publication.	

Key or legend to abbreviations and acronyms used in the safety data sheet

NF SIIPPI IFS

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

 TWA
 TWA (time-weighted average)

 Ceiling
 Maximum limit value

 C
 Carcinogen

 Section 11: TOXICOLOGICAL INFORMATION

 LD50 (lethal dose)

 Section 12: Ecological information

 EC50 (effective concentration)

STEL

STEL (Short Term Exposure Limit) Skin designation

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

Kevmor Trade Supplies

11 Belmont Avenue, Belmont WA 6104 P: 08 9277 7177 E: sales@kevmor.com.au W: kevmor.com.au