

11 Belmont Avenue
BELMONT WA 6104

W: Kevmor.com.au
E: sales@kevmor.com.au
P: (08) 9277 7177



Carpet Saver Specification & Information Sheet

Roll Size: 1.0m x 1.5m Film Thickness: 105um polyethylene (nominal) Colour: Clear
Adhesive: >1500g per 50mm with pressure sensitive Acrylic Solvent Coating (nontoxic)
(full specifications available upon request)

Before using this product, read product information, application instructions and limited warranty.

Designed Specifically For Use On Carpet Only

Carpet Saver Film is a self-adhering clear 105um (nominal) polyethylene film with pressure sensitive Acrylic coating on one side for temporary carpet protection. Use to protect carpet from heavy foot traffic during remodelling, moving, parties & painting etc. Rolls out like carpet with adhesive side out for ease of application.

This film is designed for application to synthetic carpet and can be easily removed without leaving any residue.

NOTE: DO NOT APPLY OVER DAMP CARPETING OR SUBJECT TO MOISTURE ACCUMULATION

Freshly cleaned carpet must be allowed to dry completely for minimum of 10 days. Test before fully applying.

This product should not be left in place for more than 45 days. Examine periodically and remove or replace as necessary, if exposed to high temperature, direct sunlight or other extreme conditions of temperature and time.

Storage: This product should not be stored or be attempted to be used in extremely hot (over 38c), or cold (below 2c) temperatures. This film cannot be recycled after use and should be disposed of properly. Shipping containers and core are recyclable.

APPLICATION

1. Remove from box and retain carton for future storage.
2. Locate the end, cut off film and pull out several inches to determine the unwind direction.
3. Apply pressure to first sq ft or 300mm of unwound film so it adheres firmly to carpeting.
4. Using a push broom or applicator on long runs to make it firmly adhere.
5. Unroll to desired length and reposition if necessary.
6. Carefully raise the roll off the carpet and cut with scissors or sharp blade away from you.
7. When finished fold back a small edge back against the roll itself to use next time.

Q & A

Q: What is Carpet Saver Protection. **A: Carpet Saver is a tough 105um(nominal) Polyethylene film, it adheres to synthetic carpet to help protect it from damage and maintain the original surface.**

Q: What and where is the Adhesive. **A: The adhesive is an Acrylic Solvent (nontoxic) on the outside of the roll.**

Q: How long can I leave it down. **A: May left down between 45 days maximum. (examine periodically).**

Q: How do I remove it. **A: Find a suitable edge or corner and lift with fingernail or blunt instrument and pull up**

Q. Can I use it on every kind of carpet. **A: Recommended for Synthetic carpets only. Due to many varying surfaces in Natural Fibres such as Berber, adhesive may leave residue behind on removal. However many people have used our product successfully on natural fibre products without any residue left. This was achieved by constant monitoring and testing while in position. (we cannot warrant this application).**

Q: Can this be used on other surfaces. **A: NO, is specifically designed for Carpet.**

Q: Oops I accidentally put it on the wrong surface or left it down to long, How do I clean it.

A: If carpet protection should happen to be applied or left down to long, Citrus based cleaners are generally effective in removing the residue, test on a small area first for suitability and or contact the supplier/manufacturer for advice.

Q: Can Carpet Saver be exposed to Direct Sunlight. **A: No, the product is not UV Stabilized.**

Q: can it be reused. **A: No, not reusable.**

Limited Warranty

The sole obligation of the manufacturer, distributor or seller of this product shall be to replace. If notified of defect within six(6) months of the date of purchase, such quantity of the product as is proved defective, and shall not be liable for injury loss or damage either direct or consequential arising out of the with or inability to use the product. Product should be tested for suitability prior to use and purchaser assumes the risk & liability whatever in connection therewith to use the product. This limited warranty offered in connection with the manufacturer and sale of the product is exclusive and in lien of any other warranties, express, implied, or statutory including without limitation warranty of fitness for a particular use.