



# Eco Prim Grip

**Multi-purpose, ready-to-use bonding promoter primer with a very low emission of volatile organic compounds (VOC) for render, smoothing and levelling compounds and adhesives for ceramic tiles**



## WHERE TO USE

Multi-purpose, ready-to-use primer for internal and external floors and walls.

**Eco Prim Grip** may be used to improve the bond of all types of cement, gypsum and lime-based plasters on substrates made from concrete, brickwork, vibro-compressed concrete blocks, lightweight blocks and gypsum.

**Eco Prim Grip** is also suitable for improving the bond of adhesives for ceramics, smoothing and levelling compounds on non-absorbent surfaces, such as ceramic, terrazzo and natural stone floors.

## Some application examples

- Application of render on concrete, brickwork, substrates, etc.
- Application of smoothing and levelling compounds on old ceramic, terrazzo and natural stone floors.
- Laying ceramic and natural stone floors directly on top of old ceramic floors.

## TECHNICAL CHARACTERISTICS

**Eco Prim Grip** is a solvent-free, primer composed of synthetic resin in water dispersion and selected inert materials with excellent bond strength, resistance to water and ageing. It guarantees a rough keying surface ideal for render, smoothing and levelling compounds, thus ensuring an excellent bond on smooth substrates and substrates with low absorbency, reducing and evening out absorption of water of absorbent surfaces. Once dry, it guarantees

a tough bond of any cementitious render on various types of substrate: concrete, lightweight cellular cement blocks, bricks, stone, plasterboard, wood, ceramic, metal, render, gypsum, etc.

**Eco Prim Grip** is a ready-to-use grey latex which is easy to apply using either a roller or a brush.

**Eco Prim Grip** is non-flammable and has an extremely low emission level of volatile organic compounds (VOC). Therefore, the product is considered non-hazardous for those who use the product and final users of the environments where it is applied. It may also be stored without taking particular precautions.

## RECOMMENDATIONS

- Apply at temperatures between +5°C and +35°C.
- Do not use **Eco Prim Grip** in the presence of rising damp or rising humidity, and on continuously immersed surfaces.
- **Eco Prim Grip** is ready-to-use, no dilution is required.
- Do not use as adhesion promoter for adhesives and levelling compounds on screeds and power-trowelled concrete. In such cases use **Eco Prim T**.

## APPLICATION PROCEDURE

### Preparation of the substrate

Substrates must be clean, dry, well-cured and free from oil, grease, cement laitance and loose parts.

# Eco Prim Grip



Application of Eco Prim Grip on concrete by roller



Application of Eco Prim Grip on concrete by brush



Application of render on Eco Prim Grip

## TECHNICAL DATA (typical values)

### PRODUCT IDENTITY

Consistency:	creamy liquid
Colour:	grey
Density (g/cm <sup>3</sup> ):	1.48
pH:	8.5
Dry solids content (%):	70
EMICODE:	EC1 Plus - extremely low emission level

### APPLICATION DATA (at +23°C - 50% R.H.)

Application temperature range:	from +5°C to +35°C
Waiting time before applying render:	15-20 minutes (dependant on substrate's temperature and porosity)
Waiting time before applying smoothing compound:	30 minutes (dependant on substrate's temperature and porosity)

### FINAL PERFORMANCE

Resistance to humidity:	excellent
Resistance to ageing:	excellent
Resistance to solvents and oils:	fair
Resistance to acids and alkalis:	fair
Resistance to temperatures:	excellent

There is no need to wet the surface before applying **Eco Prim Grip**.

#### Application

**Eco Prim Grip** may be applied to the substrate with either a roller or by brush or roller. The render or smoothing and levelling compound may be applied once **Eco Prim Grip** is dry. The minimum waiting time is from 15 to 60 minutes according to the surrounding conditions and the absorption of the substrate. It's possible to apply a second coat of **Eco Prim Grip** from the application of the first coat after a long time.

#### Cleaning

While still fresh, **Eco Prim Grip** may be

removed easily from floors, walls and tools with water. Once dry, it must be removed with alcohol or **Pulicol 2000**.

#### CONSUMPTION

Consumption varies between 0.20 and 0.30 kg/m<sup>2</sup> according to the absorption of the substrate.

#### PACKAGING

**Eco Prim Grip** is available in 5 and 10 kg drums.

#### STORAGE

**Eco Prim Grip** remains stable for at least 12 months under normal conditions in its original, sealed packaging.

## SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

**Eco Prim Grip** is not considered dangerous according to the current regulations regarding the classification of mixtures. During use wear protective gloves and goggles and take the usual precautions for the handling chemicals. For further and complete information about the safe use of our product please refer to the latest version of our Material Safety Data Sheet.

PRODUCT FOR PROFESSIONAL USE.

### WARNING

*Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.*

Please refer to the current version of the Technical Data Sheet, available from our website [www.mapei.com](http://www.mapei.com)

## LEGAL NOTICE

**The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.**

**The most up-to-date TDS can be downloaded from our website [www.mapei.com](http://www.mapei.com).**

**ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.**



This symbol is used to identify Mapei products which give off a low level of volatile organic compounds (VOC) as certified by GEV (Gesellschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.), an international organisation for controlling the level of emissions from products used for floors.



**Our Commitment To The Environment**  
More than 150 MAPEI products assist Project Designers and Contractors create innovative LEED (The Leadership in Energy and Environmental Design) certified projects, in compliance with the U.S. Green Building Council.

**All relevant references for the product are available upon request and from [www.mapei.com](http://www.mapei.com)**



Application of Eco Prim Grip by roller on existing terrazzo flooring



Application of Eco Prim Grip by roller on existing porcelain tiles



Application of Ultraplan self-levelling smoothing compound on dry Eco Prim Grip on old floor

**Eco Prim  
Grip**



**KEVMOR**  
TRADE SUPPLIES

**Kevmor Trade Supplies**

11 Belmont Avenue, Belmont WA 6104

P: 08 9277 7177

E: [sales@kevmor.com.au](mailto:sales@kevmor.com.au)

W: [kevmor.com.au](http://kevmor.com.au)



**BUILDING THE FUTURE**