

9

Section 1: Identification

GHS Product identifier

Mixture identification:

Trade name: MAPEPRIM SP comp.A Trade code: 901541

Recommended use of the chemical and restrictions on use

Recommended use: Water-borne synthetic resin based primer

Uses advised against: no data available

Supplier's details

Company: MAPEI AUSTRALIA Pty Ltd

180 Viking Drive Wacol QLD 4076 Australia

T. +61 7 32765000 (Mon-Fri 8am to 4.30pm)

F. +61 7 32765076

Responsable: sales@mapei.com.au

Emergency phone number

Australian Poisons Information Centre 24 Hour Service 13 11 26 Police or Fire Brigade 000

Section 2: Hazard(s) identification



Classification of the Hazardous chemical

Skin irritation, Category 2Causes skin irritation.Eye irritation, Category 2ACauses serious eye irritation.Skin Sensitisation, Category 1AMay cause an allergic skin reaction.Long-term (chronic) aquatic hazard - Category 3Harmful to aquatic life with long lasting effects.Adverse physicochemical, human health and environmental effects:

No other hazards

GHS label elements, including precautionary statements

Pictograms and Signal Words



Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

•					
P261	Avoid breathing mist/vapours/spray.				
P264	Wash hands t	Wash hands thoroughly after handling.			
P273	Avoid release	Avoid release to the environment.			
P280	Wear protecti	ve gloves/clothing an	d eye/face protection.		
P302+P352	IF ON SKIN: \	IF ON SKIN: Wash with plenty of water.			
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.				
P321	Specific treatment (see supplementary instructions on this label)				
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.				
P337+P313	If eye irritation persists: Get medical advice/attention.				
P362+P364	Take off contaminated clothing and wash it before reuse.				
Print date	14/03/2023	Production Name	MAPEPRIM SP comp.A	Page n.	1 of

P501

Dispose of contents/container in accordance with applicable regulations.

Other hazards which do not result in a classification

Other Hazards: No other hazards

This preparation contains low molecular weight epoxy resins. Cross sensitisation to other epoxies is possible. Avoid also exposure to spray mist and vapour.

Section 3: Composition and information on ingredients

Substances

no data available

Mixtures

Mixture identification: MAPEPRIM SP comp.A

Hazardous components within the meaning of the "Australian Work Health and Safety (WHS)" regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥10 - <20 %	calcium carbonate	CAS:1317-65-3 EC:215-279-6		
≥5 - <10 %	bis-[4-(2,3- epoxipropoxi)phenyl]propane	CAS:1675-54-3, 25085-99-8 EC:216-823-5 Index:603-073-	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2A, H319 Aquatic Chronic 2, H411	01-2119456619-26
		00-2	Specific Concentration Limits: C \geq 5%: Skin Irrit. 2 H315 C \geq 5%: Eye Irrit. 2A H319	
≥1 - <2.5 %	Formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol	CAS:9003-36-5 EC:701-263-0	Skin Irrit. 2, H315; Aquatic Chronic 2, H411; Skin Sens. 1, H317	01-2119454392-40-XXXX
≥1 - <2.5 %	oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	CAS:68609-97-2 EC:271-846-8 Index:603-103- 00-4	Skin Irrit. 2, H315; Skin Sens. 1B, H317	01-2119485289-22-XXXX

Section 4: First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Symptoms caused by exposure

Eye irritation

Eye damages

Skin Irritation

Erythema

Medical attention and special treatment

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Section 5: Firefighting measures

Suitable extinguishing media

None in particular. Water. Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: no data available

Explosive properties: ==

Oxidizing properties: no data available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

HazChem Code/Emergency Action code

N.A.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

Retain contaminated washing water and dispose it.

Section 7: Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Section 8: Exposure controls and personal protection Control parameters – exposure standards, biological monitoring

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
calcium carbonate CAS: 1317-65-3	OSHA		Long Term: 15 mg/m3
	OSHA		Long Term: 5 mg/m3
	National	GREECE	Long Term: 10 mg/m3
	National	GREECE	Long Term: 5 mg/m3
	National	BELGIUM	Long Term: 10 mg/m3
	National	CZECH REPUBLIC	Long Term: 10 mg/m3
	National	HUNGARY	Long Term: 10 mg/m3
	National	ESTONIA	Long Term: 10 mg/m3
	National	ESTONIA	Long Term: 5 mg/m3
	National	SLOVAKIA	Long Term: 10 mg/m3

National	UNITED KINGDOM	Long Term:	10 mg/m3; Short Term: 30 mg/m3
National	UNITED KINGDOM	Long Term:	10 mg/m3; Short Term: 12 mg/m3
National	UNITED KINGDOM	Long Term:	4 mg/m3; Short Term: 30 mg/m3
National	BULGARIA	Long Term:	10 mg/m3
National	ROMANIA	Long Term:	10 mg/m3
National	CROATIA	Long Term:	4 mg/m3
National	CROATIA	Long Term:	10 mg/m3
National	FRANCE	Long Term:	10 mg/m3

Predicted No Effect Concentration (PNEC) values

Formaldehyde, oligomeric
reaction products with 1-
chloro-2,3-epoxypropane
and phenol
CAS: 9003-36-5Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l
Sewage treatments; PNEC Limit: 0,003 mg/l
Exposure Route: Fresh Water; PNEC Limit: 0,003 mg/l
Exposure Route: Marine water; PNEC Limit: 0,294 mg/kg
Exposure Route: Marine water; PNEC Limit: 0,0003 mg/l
Exposure Route: Soil; PNEC Limit: 0,237 mg/kgoxirane, mono[(C12-14-
alkyloxy)methyl] derivs.
CAS: 68609-97-2Exposure Route: Marine water; PNEC Limit: 0,00072 mg/lExposure Route: Fresh Water; PNEC Limit: 0,0072 mg/lExposure Route: Fresh Water; PNEC Limit: 0,0072 mg/l

Exposure Route: Fresh Water; PNEC Limit: 0,0072 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 66,77 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 6,677 mg/kg
Exposure Route: Soil; PNEC Limit: 80,12 mg/kg
Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

Appropriate engineering controls

no data available

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; AS/NZS 2161.10:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to AS/NZS 1715-1716 for information on selection and use of appropriate respiratory protection equipment. no data available

Section 9: Physical and chemical properties

Physical state: Liquid Appearance: paste Color: Blue Odour: Characteristic pH: 6.50 Melting point / freezing point: no data available Initial boiling point and boiling range: 100 °C (212 °F) Flash point: no data available Evaporation rate: no data available Flammability (Solid, Gas) no data available Lower and upper explosion limit/flammability limits: no data available Vapour pressure: no data available Vapour density: no data available Relative density: 1.20 g/cm3 Solubility in water: dispersible Solubility in oil: insoluble Partition coefficient (n-octanol/water): no data available Auto-ignition temperature: no data available Decomposition temperature: no data available Kinematic viscosity: no data available VOC % (Volatile Organic Compound) : 12,6 (A+B) (Rule 1113) g/l

Particle characteristics:

Particle size: no data available Particle size distribution: no data available Shape and aspect ratio: no data available Specific surface area: no data available

Section 10: Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

no data available Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

calcium carbonate

Section 11: Toxicological information Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin irritation, Category 2(H315)
c) serious eye damage/irritation	The product is classified: Eye irritation, Category 2A(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sensitisation, Category 1A(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met
Toxicological information on main com	ponents of the mixture:

LD50 Oral Rat > 5000 mg/kg

bis-[4-(2,3-	a) acute tox	cicity LD50	Skin Rabbit = 20 mg/kg
Print date	14/03/2023	Production Name	MAPEPRIM SP comp.A

a) acute toxicity

epoxipropoxi)phenyl] propane		
		LD50 Oral Rat = 11300 µL/kg
		LD50 Skin Rabbit = 20000 mg/kg
Formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenol	a) acute toxicity	LD50 Oral Rat > 5000, mg/kg
		LD50 Skin Rat > 2000 mg/kg
	i) STOT-repeated exposure	NOAEL Oral = 250 mg/kg
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	a) acute toxicity	LD50 Oral Rat = 19200 mg/kg
		LD50 Skin Rabbit = 4000, mg/kg

Section 12: Ecological information Ecotoxicity

· \ 1

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

Harmful to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Long-term (chronic) aquatic hazard - Category 3(H412)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
calcium carbonate	CAS: 1317-65-3 - EINECS: 215- 279-6	a) Aquatic acute toxicity : LC50 Fish > 10000 mg/L 96
		a) Aquatic acute toxicity: EC50 Daphnia > 1000 mg/L 48
		a) Aquatic acute toxicity : EC50 Algae > 200 mg/L 72
Formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol	CAS: 9003-36-5 - EINECS: 701- 263-0	a) Aquatic acute toxicity : LC50 Fish = 5,7 mg/L 96h
		a) Aquatic acute toxicity : EC50 Daphnia = 2,55 mg/L 48h
		a) Aquatic acute toxicity : EC50 Algae = 1,8 mg/L 72h
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	CAS: 68609-97- 2 - EINECS: 271-846-8 - INDEX: 603- 103-00-4	a) Aquatic acute toxicity : LC50 Fish > 100 mg/L 96h
		a) Aquatic acute toxicity : EL50 Daphnia = 7,2 mg/L 48h
		a) Aquatic acute toxicity : EC50 Algae = 843 mg/L 72h
		b) Aquatic chronic toxicity : NOEC Algae = 500 mg/L 72h

Persistence and degradability

Component

Persitence/Degradability:

oxirane, mono[(C12-14-Readily biodegradable alkyloxy)methyl] derivs.

Bioaccumulative potential

oxirane, mono[(C12-14-

alkyloxy)methyl] derivs.

Component

Bioaccumulation

Not bioaccumulative

Mobility in soil

no data available

Other adverse effects

no data available

Section 13: Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

no data available

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

Section 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

UN number

no data available

UN proper shipping name

no data available

Transport hazard class(es)

no data available

Packing group, if applicable

no data available

Environmental hazards

no data available

Special precautions for user

ADG-Subsidiary hazards no data available

ADG-S.P.: no data available

Road and Rail (ADR-RID):

no data available

ADR-Hazard identification number: NA

Air (IATA):

no data available

Sea (IMDG):

no data available Additional Information

no data available

HazChem Code/Emergency Action code

no data available

Section 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Australian Work Health and Safety (WHS) act and the Code of Practice on preparation of safety data sheets for Hazardous Chemicals.

AICIS: all components are listed

Section 16: Any other relevant information

Code Description

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1B	Skin Sens. 1B	Skin Sensitisation, Category 1B
AUS-HAE/C2	Aquatic Chronic 2	Long-term (chronic) aquatic hazard - Category 2

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

 $\ensuremath{\mathsf{IRCCS}}$: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 16. OTHER INFORMATION