Version: April 13th, 2010

MAPEI®

Ultrabond® 2185

Premium Commercial Carpet Seam Adhesive

DESCRIPTION

Ultrabond 2185 commercial carpet seam adhesive is a solvent-based formulation specifically designed to prevent edge raveling, and to seal seams of most commercial and outdoor carpets. *Ultrabond 2185* is fast-setting and waterproof. It is also compatible with most carpet backings, and is excellent for direct-glue and double-glue applications.

FEATURES AND BENEFITS

- Prevents edge raveling
- Fast-setting and waterproof
- Ultraviolet (UV) tracer built-in

INDUSTRY STANDARDS AND APPROVALS

CRI #104 – Standard for Installation Specification of Commercial Carpet
CRI #105 – Standard for Installation of Residential Carpet

WHERE TO USE

- Interior/exterior residential and commercial carpet installations

LIMITATIONS

- Do not use to seam vinyl-backed carpet products.

SURFACE PREPARATION

- Ensure that carpet seam and seam area are clean, dry and free of loose particles and any other foreign matter that may reduce or prevent proper adhesion.

MIXING

- Ready to use; no mixing necessary

Choose all appropriate safety equipment before use. Refer to Material Safety Data Sheet (MSDS) for more information.

PRODUCT APPLICATION

1. Turn off all sources of ignition including pilot lights on HVAC and hot-water tanks.
2. Keep away from heat, sparks or open flames of any kind. Use only in well-ventilated areas, open windows and doors. Do not smoke in work area.
3. Read all instructions thoroughly before installation.
4. Open bottle and remove safety seal.
5. Replace spout and cut tip back 1/4" (6 mm) from end.
6. Using gentle pressure on bottle, apply a 1/4" (6 mm) bead of *Ultrabond 2185* to the carpet edge, taking care to not get material on face yarn.
7. Roll seam together, using a carpet tractor to ensure proper bond.

CLEANUP

Promptly clean any adhesive using *Ultrabond 5085* adhesive remover.

Product Performance Properties

Laboratory Tests	Results
Polymer type	Synthetic rubber
Percent solids	28%
VOCs (Rule #1168 of California's SCAQMD)	> 550 g/L
Density	6.83 lbs. per U.S. gal. (0,818 g per mL)
Consistency	Liquid
Color	Translucent amber
Shelf life	1 year when stored in original packaging at 73°F (23°C)
Storage conditions	40°F to 100°F (4°C to 38°C)
Flash point (Tag)	< 20°F (-7°C)

Packaging

Product Code	Size
94791 (U.S. only)	1 U.S. qt. (946 mL)

Approximate Product Coverage*

580-640 linear ft. per U.S. qt. (177 to 195 linear m per 946 mL)

**Coverages shown are for estimating purposes only. Actual jobsite coverages may vary according to substrate conditions and setting practices.*

Refer to MAPEI's Material Safety Data Sheet (MSDS) for specific data related to VOCs, health and safety, and handling of product.

STATEMENT OF RESPONSIBILITY

Before using, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

We proudly support the following industry organizations:

MAPEI Headquarters of the Americas
1144 East Newport Center Drive
Deerfield Beach, Florida 33442
Phone: 1-888-US-MAPEI
(1-888-876-2734)

Technical Services
1-800-992-6273 (U.S. and Puerto Rico)
1-800-361-9309 (Canada)

Customer Service
1-800-42-MAPEI (1-800-426-2734)

For the most current BEST-BACKED™ product data and warranty information, visit www.mapei.com.

Edition Date: March 10, 2010

PR5754 2185D_C10Evp © 2010 MAPEI Corporation. All Rights Reserved. Printed in the USA.